

Package ‘ellipse’

March 17, 2012

Version 0.3-7

Date 2012-03-17

Title Functions for drawing ellipses and ellipse-like confidence regions

Author Duncan Murdoch <murdoch@stats.uwo.ca> and E. D. Chow (porting to R by Jesus M. Frias Celayeta <iosu@bureau.ucc.ie>)

Maintainer Duncan Murdoch <murdoch@stats.uwo.ca>

Description This package contains various routines for drawing ellipses and ellipse-like confidence regions, implementing the plots described in Murdoch and Chow (1996), A graphical display of large correlation matrices, *The American Statistician* 50,178-180. There are also routines implementing the profile plots described in Bates and Watts (1988), *Nonlinear Regression Analysis and its Applications*.

Depends R (>= 2.0.0),graphics,stats

Suggests MASS

LazyLoad yes

License GPL (>= 2)

Repository CRAN

Date/Publication 2012-03-17 22:31:58

R topics documented:

ellipse-package	2
ellipse	3
ellipse.arima0	4
ellipse.glm	5
ellipse.lm	6
ellipse.nls	7
ellipse.profile	8

ellipse.profile.glm	9
ellipse.profile.nls	11
pairs.profile	12
plotcorr	13
Index	16

ellipse-package *Functions for drawing ellipses and ellipse-like confidence regions*

Description

This package contains various routines for drawing ellipses and ellipse-like confidence regions, implementing the plots described in Murdoch and Chow (1996).

There are also routines implementing the profile plots described in Bates and Watts (1988).

Details

There are three groups of routines in the ellipse package. The first consists of those involved with [plotcorr](#), which implements the plots described in Murdoch and Chow (1996). These display correlations using ellipses, whose shape is that of the contours of a bivariate normal distribution with matching correlation.

The second group implements a version of the profile plots described in Bates and Watts (1988); see [ellipse.profile](#) and [pairs.profile](#).

The last group provide the basis for the others, drawing ellipses based on various S objects, including scalar correlations, covariance matrices [arima](#), [lm](#), and [nls](#) fits: see [ellipse](#).

Author(s)

Duncan Murdoch <murdoch@stats.uwo.ca> and E. D. Chow (porting to R by Jesus M. Frias Celayeta <iosu@bureau.ucc.ie>)

Maintainer: Duncan Murdoch <murdoch@stats.uwo.ca>

References

Bates, D.M. and Watts, D.G. (1988). Nonlinear Regression Analysis and its Applications. Wiley.

Murdoch, D.J. and Chow, E.D. (1996). A graphical display of large correlation matrices. The American Statistician 50, 178-180.

ellipse	<i>Make an ellipse</i>
---------	------------------------

Description

A generic function returning an ellipse or other outline of a confidence region for two parameters.

Usage

```
ellipse(x, ...)
## Default S3 method:
ellipse(x, scale = c(1, 1), centre = c(0, 0), level = 0.95,
        t = sqrt(qchisq(level, 2)), which = c(1, 2), npoints = 100, ...)
```

Arguments

x	An object. In the default method the parameter x should be a correlation between -1 and 1 or a square positive definite matrix at least 2x2 in size. It will be treated as the correlation or covariance of a multivariate normal distribution.
...	Descendant methods may require additional parameters.
scale	If x is a correlation matrix, then the standard deviations of each parameter can be given in the scale parameter. This defaults to c(1, 1), so no rescaling will be done.
centre	The centre of the ellipse will be at this position.
level	The confidence level of a pairwise confidence region. The default is 0.95, for a 95% region. This is used to control the size of the ellipse being plotted. A vector of levels may be used.
t	The size of the ellipse may also be controlled by specifying the value of a t-statistic on its boundary. This defaults to the appropriate value for the confidence region.
which	This parameter selects which pair of variables from the matrix will be plotted. The default is the first 2.
npoints	The number of points used in the ellipse. Default is 100.

Details

The default method uses the $(\cos(\theta + d/2), \cos(\theta - d/2))$ parametrization of an ellipse, where $\cos(d)$ is the correlation of the parameters.

Value

An npoints x 2 matrix is returned with columns named according to the row names of the matrix x (default 'x' and 'y'), suitable for plotting.

References

Murdoch, D.J. and Chow, E.D. (1996). A graphical display of large correlation matrices. *The American Statistician* 50, 178-180.

See Also

[ellipse.lm](#), [ellipse.nls](#), [ellipse.profile](#), [ellipse.profile.nls](#), [ellipse.arima0](#), [plotcorr](#)

Examples

```
# Plot an ellipse corresponding to a 95% probability region for a
# bivariate normal distribution with mean 0, unit variances and
# correlation 0.8.
plot(ellipse(0.8), type = 'l')
```

ellipse.arima0

Outline an approximate pairwise confidence region

Description

This function produces the ellipsoidal outline of an approximate pairwise confidence region for an ARIMA model fit.

Usage

```
## S3 method for class 'arima0'
ellipse(x, which = c(1, 2), level = 0.95, t = sqrt(qchisq(level, 2)), ...)
```

Arguments

x	The first argument should be an arima0 object, usually resulting from a call to arima0().
which	Which selects the pair of parameters to be plotted. The default is the first two.
level	The confidence level of the region. Default 95%.
t	The t statistic on the boundary of the ellipse.
...	Other ellipse.default parameters may also be used.

Details

The summary function is used to obtain the approximate covariance matrix of the fitted parameters.

Value

A matrix with columns x and y to outline the confidence region.

See Also[ellipse](#)**Examples**

```

data(USAccDeaths)
fit <- arima0(USAccDeaths, order = c(0, 1, 1), seasonal = list(order = c(0, 1, 1)))
# Plot the approximate 95% confidence region for the first two parameters
# of the model
plot(ellipse(fit), type = 'l')
points(fit$coef[1], fit$coef[2])

```

ellipse.glm

*Outline an approximate pairwise confidence region***Description**

This function produces the ellipsoidal outline of an approximate pairwise confidence region for a generalized linear model fit.

Usage

```

## S3 method for class 'glm'
ellipse(x, which = c(1, 2), level = 0.95, t, npoints = 100,
        dispersion, ...)

```

Arguments

x	The first argument should be a glm object, usually resulting from a call to glm().
which	Which selects the pair of parameters to be plotted. The default is the first two.
level	The confidence level of the region. Default 95%.
t	The t statistic on the boundary of the ellipse. For Binomial or Poisson families, sqrt(qchisq(level, 2)) is used; for other distributions, sqrt(2*qt(level, 2, df)) where df is the residual degrees of freedom.
npoints	How many points to return in the ellipse.
dispersion	The value of dispersion to use. If specified, it is treated as fixed, and the chi-square limits for t are used. If missing, it is taken from summary(x).
...	Other ellipse.default parameters may also be used.

Details

The summary function is used to obtain the approximate covariance matrix of the fitted parameters, the dispersion estimate, and the degrees of freedom.

Value

A matrix with columns named according to which to outline the confidence region.

See Also

[ellipse.default](#)

Examples

```
## Dobson (1990) Page 93: Randomized Controlled Trial :

counts <- c(18,17,15,20,10,20,25,13,12)
outcome <- gl(3,1,9)
treatment <- gl(3,3)
glm.D93 <- glm(counts ~ outcome + treatment, family=poisson())

# Plot an approximate 95 % confidence region for the two Outcome parameters

plot(ellipse(glm.D93, which = c(2,3)), type = 'l')
points(glm.D93$coefficients[2], glm.D93$coefficients[3])
```

ellipse.lm

Outline a pairwise confidence region for a linear model fit.

Description

This function produces the ellipsoidal outline of a pairwise confidence region for a linear model fit.

Usage

```
## S3 method for class 'lm'
ellipse(x, which = c(1, 2), level = 0.95,
        t = sqrt(2 * qf(level, 2, x$df.residual)), ...)
```

Arguments

x	The first argument should be an lm object, usually resulting from a call to lm().
which	Which selects the pair of parameters to be plotted. The default is the first two.
level	The confidence level of the region. Default 95%.
t	The t statistic on the boundary of the ellipse.
...	Other ellipse.default parameters may also be used.

Details

The summary function is used to obtain the covariance matrix of the fitted parameters.

Value

A matrix with columns x and y to outline the confidence region.

See Also

[ellipse.default](#)

Examples

```
# Plot the estimate and joint 90% confidence region for the displacement and cylinder
# count linear coefficients in the mtcars dataset
data(mtcars)
fit <- lm(mpg ~ disp + cyl , mtcars)
plot(ellipse(fit, which = c('disp', 'cyl'), level = 0.90), type = 'l')
points(fit$coefficients['disp'], fit$coefficients['cyl'])
```

ellipse.nls

Outline an approximate pairwise confidence region

Description

This function produces the ellipsoidal outline of an approximate pairwise confidence region for a nonlinear model fit.

Usage

```
## S3 method for class 'nls'
ellipse(x, which = c(1, 2), level = 0.95,
        t = sqrt(2 * qf(level, 2, s$df[2])), ...)
```

Arguments

x	The first argument should be an nls object, usually resulting from a call to nls().
which	Which selects the pair of parameters to be plotted. The default is the first two.
level	The confidence level of the region. Default 95%.
t	The t statistic on the boundary of the ellipse.
...	Other ellipse.default parameters may also be used.

Details

The summary function is used to obtain the approximate covariance matrix of the fitted parameters.

Value

A matrix with columns x and y to outline the confidence region.

See Also

[ellipse.default](#), [ellipse.profile](#)

Examples

```
# Plot an approximate 95% confidence region for the weight and displacement
# parameters in the Michaelis Menten model
data(Puromycin)
fit <- nls(rate ~ Vm*conc/(K + conc), data = Puromycin, subset = state=="treated",
  start = list(K = 0.05, Vm = 200))
plot(ellipse(fit,which=c('Vm','K')), type = 'l')
params <- fit$m$getPars()
points(params['Vm'],params['K'])
```

ellipse.profile

Pairwise profile sketch

Description

This routine approximates a contour of a function based on the profile of that function.

Usage

```
## S3 method for class 'profile'
ellipse(x, which = c(1, 2), level = 0.95, t = sqrt(qchisq(level, 2)),
  npoints = 100, ...)
```

Arguments

x	An object of class profile , e.g. from profile.glm in the MASS package.
which	Which pair of parameters to use.
level	The <code>ellipse.profile</code> function defaults assume that the profiled function is -2 times the log likelihood of a regular model. With this assumption the <code>level</code> argument specifies the confidence level for an asymptotic confidence region.
t	The square root of the value to be contoured.
npoints	How many points to use in the ellipse.
...	Extra arguments are not used.

Details

This function uses the 4 point approximation to the contour as described in Appendix 6 of Bates and Watts (1988). It produces the exact contour for quadratic surfaces, and good approximations for mild deviations from quadratic. If the surface is multimodal, the algorithm is likely to produce nonsense.

Value

An `npoints` x 2 matrix with columns having the chosen parameter names, which approximates a contour of the function that was profiled.

References

Bates and Watts (1988) Nonlinear Regression Analysis & its Applications

See Also

[profile](#), [ellipse.nls](#)

Examples

```
# Plot an approximate 95% confidence region for the Puromycin
# parameters Vm and K, and overlay the ellipsoidal region

data(Puromycin)
Purboth <- nls(formula = rate ~ ((Vm + delV * (state == "treated"))
  * conc)/(K + conc), data = Puromycin,
  start = list(Vm = 160, delV = 40, K = 0.05))
Pur.prof <- profile(Purboth)
plot(ellipse(Pur.prof, which = c('Vm', 'K')), type = 'l')
lines(ellipse(Purboth, which = c('Vm', 'K')), lty = 2)
params <- Purboth$m$getPars()
points(params['Vm'],params['K'])
```

ellipse.profile.glm *Pairwise profile sketch for GLM profiles*

Description

This routine approximates a pairwise confidence region for a glm model.

Usage

```
## S3 method for class 'profile.glm'
ellipse(x, which = c(1, 2), level = 0.95, t,
  npoints = 100, dispersion, ...)
```

Arguments

<code>x</code>	An object of class <code>profile.glm</code> .
<code>which</code>	Which pair of parameters to use.
<code>level</code>	The level argument specifies the confidence level for an asymptotic confidence region.

t	The square root of the value to be contoured. By default, this is <code>qchisq(level, 2)</code> for models with fixed dispersion (i.e. binomial and Poisson), and <code>2 * qf(level, 2, df)</code> for other models, where <code>df</code> is the residual degrees of freedom.
npoints	How many points to use in the ellipse.
dispersion	If specified, fixed dispersion is assumed, otherwise the dispersion is taken from the model.
...	Extra parameters which are not used (for compatibility with the generic).

Details

This function uses the 4 point approximation to the contour as described in Appendix 6 of Bates and Watts (1988). It produces the exact contour for quadratic surfaces, and good approximations for mild deviations from quadratic. If the surface is multimodal, the algorithm is likely to produce nonsense.

Value

An `npoints x 2` matrix with columns having the chosen parameter names, which approximates a contour of the function that was profiled.

References

Bates and Watts (1988) *Nonlinear Regression Analysis & its Applications*

See Also

[profile, glm, ellipse.glm](#)

Examples

```
## MASS has a pairs.profile function that conflicts with ours, so
## do a little trickery here
noMASS <- is.na(match('package:MASS', search()))
if (noMASS) require(MASS)

## Dobson (1990) Page 93: Randomized Controlled Trial :

counts <- c(18,17,15,20,10,20,25,13,12)
outcome <- gl(3,1,9)
treatment <- gl(3,3)
glm.D93 <- glm(counts ~ outcome + treatment, family=poisson())

## Plot an approximate 95% confidence region for the two outcome variables
prof.D93 <- profile(glm.D93)
plot(ellipse(prof.D93, which = 2:3), type = 'l')
lines(ellipse(glm.D93, which = 2:3), lty = 2)
params <- glm.D93$coefficients
points(params[2],params[3])

## Clean up our trickery
```

```
if (noMASS) detach('package:MASS')
```

```
ellipse.profile.nls Pairwise profile sketch
```

Description

This routine approximates a pairwise confidence region for a nonlinear regression model.

Usage

```
## S3 method for class 'profile.nls'
ellipse(x, which = c(1, 2), level = 0.95, t = sqrt(2 * qf(level, 2, attr(x, "summary")$df[2])),
        npoints = 100, ...)
```

Arguments

x	An object of class profile.nls .
which	Which pair of parameters to use.
level	The level argument specifies the confidence level for an asymptotic confidence region.
t	The square root of the value to be contoured.
npoints	How many points to use in the ellipse.
...	Extra parameters which are not used (for compatibility with the generic).

Details

This function uses the 4 point approximation to the contour as described in Appendix 6 of Bates and Watts (1988). It produces the exact contour for quadratic surfaces, and good approximations for mild deviations from quadratic. If the surface is multimodal, the algorithm is likely to produce nonsense.

Value

An npoints x 2 matrix with columns having the chosen parameter names, which approximates a contour of the function that was profiled.

References

Bates and Watts (1988) Nonlinear Regression Analysis & its Applications

See Also

[profile](#), [ellipse.nls](#)

Examples

```
# Plot an approximate 95% confidence region for the Puromycin
# parameters Vm and K, and overlay the ellipsoidal region
data(Puromycin)
Purboth <- nls(formula = rate ~ ((Vm + delV * (state == "treated"))
  * conc)/(K + conc), data = Puromycin,
  start = list(Vm = 160, delV = 40, K = 0.05))
Pur.prof <- profile(Purboth)
plot(ellipse(Pur.prof, which = c('Vm', 'K')), type = 'l')
lines(ellipse(Purboth, which = c('Vm', 'K')), lty = 2)
params <- Purboth$m$getPars()
points(params['Vm'],params['K'])
```

pairs.profile

Profile pairs

Description

This function produces pairwise plots of profile traces, profile sketches, and ellipse approximations to confidence intervals.

Usage

```
## S3 method for class 'profile'
pairs(x, labels = c(names(x), "Profile tau"), panel = lines, invert = TRUE,
  plot.tau = TRUE, plot.trace = TRUE, plot.sketch = TRUE,
  plot.ellipse = FALSE, level = 0.95, ...)
```

Arguments

x	An object of class profile, generally the result of the profile() function.
labels	The labels to use for each variable. These default to the variable names.
panel	The function to use to draw the sketch in each panel.
invert	Whether to swap the axes so things look better.
plot.tau	Whether to do the profile tau (profile t) plots.
plot.trace	Whether to do the profile trace plots.
plot.sketch	Whether to do the profile sketch plots.
plot.ellipse	Whether to do the ellipse approximations.
level	The nominal confidence level for the profile sketches and ellipses.
...	Other plotting parameters.

Details

This function implements the plots used in Bates and Watts (1988) for nonlinear regression diagnostics.

Side Effects

Produces a plot on the current device for each pair of variables in the profile object.

References

Bates and Watts (1988), Nonlinear Regression Analysis & its Applications.

See Also

[profile](#), [ellipse.profile](#), [ellipse.nls](#)

Examples

```
# Plot everything for the Puromycin data
data(Puromycin)
Purboth <- nls(formula = rate ~ ((Vm + delV * (state == "treated"))
  * conc)/(K + conc), data = Puromycin,
  start = list(Vm = 160, delV = 40, K = 0.05))
Pur.prof <- profile(Purboth)
pairs(Pur.prof, plot.ellipse = TRUE)
```

plotcorr

Plot correlation matrix ellipses

Description

This function plots a correlation matrix using ellipse-shaped glyphs for each entry. The ellipse represents a level curve of the density of a bivariate normal with the matching correlation.

Usage

```
plotcorr(corr, outline = TRUE, col = 'grey', numbers = FALSE, type = c("full", "lower", "upper"),
  diag = (type == "full"), bty = "n", axes = FALSE, xlab = "", ylab = "", asp = 1,
  cex.lab = par("cex.lab"), cex = 0.75*par("cex"), mar = 0.1 + c(2,2,4,2), ...)
```

Usage

```
plotcorr(corr, outline = TRUE, col = "grey", numbers = FALSE,
  type = "full", diag = FALSE, ...)
```

Arguments

corr	A matrix containing entries between -1 and 1 to be plotted as correlations.
outline	Whether the ellipses should be outlined in the default colour.
col	Which colour(s) to use to fill the ellipses.

numbers	Whether to plot numerical correlations in place of ellipses. If numbers is TRUE, then the correlations will be rounded to a single decimal place and placed on the plot.
type	Character. Plot "full" matrix or just "upper" or "lower" triangular part of it.
diag	Logical. Plot diagonal elements or not.
...	Additional graphical parameters.

Details

The ellipses being plotted will be tangent to a unit character square, with the shape chosen to match the required correlation. If `numbers = FALSE`, the `col` vector will be recycled to colour each of the ellipses; if TRUE, it will be ignored.

Author(s)

Duncan Murdoch; Gregor Gorjanc suggested the `type` and `diag` options.

References

Murdoch, D.J. and Chow, E.D. (1996). A graphical display of large correlation matrices. *The American Statistician* 50, 178-180.

See Also

[ellipse](#)

Examples

```
save.par <- par(ask = interactive())

# Plot the correlation matrix for the mtcars data full model fit
data(mtcars)
fit <- lm(mpg ~ ., mtcars)
plotcorr(summary(fit, correlation = TRUE)$correlation)

# Plot a second figure with numbers in place of the
# ellipses
plotcorr(summary(fit, correlation = TRUE)$correlation, numbers = TRUE)

# Colour the ellipses to emphasize the differences. The color range
# is based on RColorBrewer's Reds and Blues (suggested by Gregor Gorjanc)

corr.mtcars <- cor(mtcars)
ord <- order(corr.mtcars[1,])
xc <- corr.mtcars[ord, ord]
colors <- c("#A50F15", "#DE2D26", "#FB6A4A", "#FCAE91", "#FEE5D9", "white",
            "#EFF3FF", "#BDD7E7", "#6BAED6", "#3182BD", "#08519C")
plotcorr(xc, col=colors[5*xc + 6])

plotcorr(xc, col=colors[5*xc + 6], type = "upper")
plotcorr(xc, col=colors[5*xc + 6], type = "lower", diag = TRUE)
```

plotcorr

15

par(save.par)

Index

- *Topic **dplot**
 - ellipse, 3
 - ellipse-package, 2
 - ellipse.arima0, 4
 - ellipse.glm, 5
 - ellipse.lm, 6
 - ellipse.nls, 7
 - ellipse.profile, 8
 - ellipse.profile.glm, 9
 - ellipse.profile.nls, 11
 - pairs.profile, 12
 - *Topic **hplot**
 - plotcorr, 13
 - *Topic **models**
 - ellipse.profile, 8
 - ellipse.profile.glm, 9
 - ellipse.profile.nls, 11
 - *Topic **nonlinear**
 - ellipse.nls, 7
 - pairs.profile, 12
 - *Topic **package**
 - ellipse-package, 2
 - *Topic **regression**
 - ellipse.glm, 5
 - ellipse.lm, 6
 - pairs.profile, 12
 - *Topic **ts**
 - ellipse.arima0, 4
- arima, 2
- ellipse, 2, 3, 5, 14
- ellipse-package, 2
- ellipse.arima0, 4, 4
- ellipse.default, 6–8
- ellipse.glm, 5, 10
- ellipse.lm, 4, 6
- ellipse.nls, 4, 7, 9, 11, 13
- ellipse.profile, 2, 4, 8, 8, 13
- ellipse.profile.glm, 9
- ellipse.profile.nls, 4, 11
- glm, 10
- lm, 2
- nls, 2
- pairs.profile, 2, 12
- plotcorr, 2, 4, 13
- profile, 8–11, 13
- profile.glm, 8, 9
- profile.nls, 11